

# AENOR

ENEC Certification Body registered under ID # 01. For further information, please consult [www.enec.com](http://www.enec.com)

## LICENCE

to use the European Mark



**Licence Nr.** ENEC/001308

**Under the conditions given in the following pages of this document, the licence to use the ENEC Mark in conjunction with the suffix 01, as shown above, has been issued to:**

NORMAGRUP TECHNOLOGY, S.A.  
Parque TECNOLÓGICO ASTURIAS  
33428 LLANERA (Asturias – España / Spain)

**For the product(s):**

Fixed general purpose luminaire

**Trade name(s):**

NORMALIT

**Complying with the following European Standards:**

EN IEC 60598-1:2021; EN IEC 60598-1:2021/A11:2022;  
EN IEC 60598-2-1:2021

**Date:** 2025-07-22

**Signature:**

A handwritten signature in blue ink, appearing to read 'Rafael García', with a long horizontal stroke extending to the right.

**Name:** Rafael García  
**Position:** Chief Executive Officer

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

AENOR CONFÍA, S.A.U.  
Cl Génova, 6  
28004 MADRID (Spain)

## CERTIFICATE OF THE ENEC EUROPEAN MARK

Type of Product	FIXED GENERAL PURPOSE LUMINAIRE
r1) Certificate n°	ENEC/001308
r2) Date of the Certificate	2025-07-22
r3) report n°	2024120647B1
r4) Name and address of the licensee	NORMAGRUP TECHNOLOGY, S.A. Parque TECNOLÓGICO ASTURIAS 33428 LLANERA (Asturias - España / Spain)
r5) Address of the factory	PQ TECNOLÓGICO ASTURIAS - PARCELA, 10 33428 LLANERA (Asturias - España / Spain)
r6) European Standard	EN IEC 60598-1:2021; EN IEC 60598-1:2021/A11:2022; EN IEC 60598-2-1:2021
r7) Type reference	See above for details
r8) Trade mark	NORMALIT
r9) Rated voltage and frequency	220-240V~ 50/60 Hz
r10) N° of lamps and rated wattage	See above for details
r11) Type of lamps and lampholder	LED module; SMD
r12) Degree of protection (IP)	IP 66
r13) Power supply connection means	Terminal block on the driver
r14) Class. respect supporting material	Suitable for normally flammable surfaces
r15) Protection against electric shock (class)	Class I
r16) Limitations	Horizontal fixing. Ta max. = 25 °C
r17) Additional data	See above for details
Date of expiry: 2029-02-01	

## CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Nº of lamps and rated wattage	Additional data
BNE100-4DFN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-4DMN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-4DSN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-4FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-4MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-4SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BNE100-5DFN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-5DMN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-5DSN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-5FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-5MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-5SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BNE100-6DFN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE100-6DMN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE100-6DSN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE100-6FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE100-6MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE100-6SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BNE150-4DMN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE150-4DSN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE150-4FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE150-4MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE150-4SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE150-5DMN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE150-5DSN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE150-5FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE150-5MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE150-5SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE150-6DMN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE150-6DSN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE150-6FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE150-6MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE150-6SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-4DFN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-4DMN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-4DSN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-4FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-4MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-4SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BNE200-5DFN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE200-5DMN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K

## CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Nº of lamps and rated wattage	Additional data
BNE200-5DSN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE200-5FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE200-5MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE200-5SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BNE200-6DFN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-6DMN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-6DSN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-6FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-6MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BNE200-6SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN100-4FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BN100-4MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BN100-4SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 4000 K
BN100-5FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BN100-5MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BN100-5SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 5700 K
BN100-6FN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BN100-6MN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BN100-6SN	1 x 90 W máx.	Blok Next Series. 240 mm Ø, 6500 K
BN150-4FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN150-4MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN150-4SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN150-5FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN150-5MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN150-5SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN150-6FN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN150-6MN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN150-6SN	1 x 135 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN200-4FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN200-4MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN200-4SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 4000 K
BN200-5FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN200-5MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN200-5SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 5700 K
BN200-6FN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN200-6MN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K
BN200-6SN	1 x 180 W máx.	Blok Next Series. 260 mm Ø, 6500 K