

Cyre P

Cyre P is the wall mounted version of the CYRE luminaire. Based on an cylindric extruded aluminium profile and a faceted reflector made in high reflection polycarbonate.

Cyre P

Installation	Wall surface mounted
Diffuser	○
Light source	LED
Photobiological safety	1
UGR	19
CRI	>80
MacAdam ellipse	3
Beam angle range	94
Power range (W)	6,4
Colour temperature (°K)	3000 4000
Light range	760-885
Power factor	0,92
Efficiency (%)	92,9
Expectancy	60000 h L70B10
DALI Option	✓
Continuous function 24h	✓
IP	20
Class	I

○ Without diffuser



For other CRI values, please contact us.



Cyre P



Wall surface mounted

LED CE 5000K

IP 20

CRI >80

UGR 19

94°


Expectancy
60000 h.
L70B10

Efficiency (%)
92,9

Photobiological safety


RG0	Risk free
RG1*	1 Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3 h.



○ RAL9016
● RAL9005

Without diffuser



	W	K	LUMEN	COLOUR	h ₉₀
AC03B	1x6,4W	3000	760 lm	○	0,6
AC03N	1x6,4W	3000	760 lm	●	0,6
AC04B	1x6,4W	4000	885 lm	○	0,6
AC04N	1x6,4W	4000	885 lm	●	0,6



Compatible with **NormaLINK**

	W	K	LUMEN	COLOUR	h ₉₀
AC03DB	1x6,4W	3000	760 lm	○	0,6
AC03DN	1x6,4W	3000	760 lm	●	0,6
AC04DB	1x6,4W	4000	885 lm	○	0,6
AC04DN	1x6,4W	4000	885 lm	●	0,6