


Hat S



IP 30

CRI >80

UGR 22

84°

Expectancy
72000 h.
L70B10


Efficiency (%)
75,1

Photobiological safety


RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3 h.

- RAL9016
- RAL7001
- RAL9005



Microprismatic diffuser



	W	K	LUMEN	COLOUR	⚙️
EHS23B	1x17W	3000	1800 lm	○	1,0
EHS23G	1x17W	3000	1800 lm	●	1,0
EHS23N	1x17W	3000	1800 lm	●	1,0
EHS24B	1x17W	4000	1900 lm	○	1,0
EHS24G	1x17W	4000	1900 lm	●	1,0
EHS24N	1x17W	4000	1900 lm	●	1,0
EHS25B	1x17W	5000	1920 lm	○	1,0
EHS25G	1x17W	5000	1920 lm	●	1,0
EHS25N	1x17W	5000	1920 lm	●	1,0
EHS26B	1x17W	6000	1920 lm	○	1,0
EHS26G	1x17W	6000	1920 lm	●	1,0
EHS26N	1x17W	6000	1920 lm	●	1,0

! 220v LED, does not need a driver

Hat S

Installation	Ceiling surface mounted Wall surface mounted
Diffuser	⊗
Light source	LED
Photobiological safety	0
UGR	22
CRI	>80
MacAdam ellipse	3
Beam angle range	84
Power range (W)	17
Colour temperature (°K)	3000 6000
Light range	1800-1920
Power factor	0,98
Efficiency (%)	75,1
Expectancy	72000 h L70B10
DALI Option	—
Continuous function 24h	✓
IP	30
Class	I

⊗ Microprismatic diffuser

! Other CRI values please contact us