

Mural

Wall mounted luminaire with direct illumination (Mural) or direct/indirect (Mural Mixto) available in three different finishes: white, grey or black.





	Mural	Mural Mixto
Installation	Wall surface mounted	Wall surface mounted
Diffuser	○	○
Light source	LED	LED
Photobiological safety	0	0
UGR	22	22
CRI	>80	>80
MacAdam ellipse	3	3
Beam angle range	–	–
Power range (W)	6,7-9,5	13,4-19
Colour temperature (°K)	3000 4000	3000 4000
Light range	760-1290	1520-2580
Power factor	0,95	0,95
Efficiency (%)	65,9	67
Expectancy	72000 h L70B10	72000 h L70B10
DALI Option	–	–
Continuous function 24h	✓	✓
IP	30	30
Class	I	I

○ Opal diffuser



For other CRI values, please contact us.



Mural



Wall surface mounted



IP 30

CRI >80 UGR 22


Photobiological safety

RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

Expectancy **72000 h.**
L70B10


Efficiency (%) **65,9**

*Time under 3 h.



- RAL9016
- RAL7001
- RAL9005


Opal diffuser



— C0-C180
— C90-C270 $\eta=66\%$

	W	K	LUMEN	COLOUR	
MD1L3B	1x6,7W	3000	760 lm	○	0,8
MD1L3G	1x6,7W	3000	760 lm	●	0,8
MD1L3N	1x6,7W	3000	760 lm	●	0,8
MD1L4B	1x6,7W	4000	840 lm	○	0,8
MD1L4G	1x6,7W	4000	840 lm	●	0,8
MD1L4N	1x6,7W	4000	840 lm	●	0,8
MD1H3B	1x9,5W	3000	1160 lm	○	0,8
MD1H3G	1x9,5W	3000	1160 lm	●	0,8
MD1H3N	1x9,5W	3000	1160 lm	●	0,8
MD1H4B	1x9,5W	4000	1290 lm	○	0,8
MD1H4G	1x9,5W	4000	1290 lm	●	0,8
MD1H4N	1x9,5W	4000	1290 lm	●	0,8

Direct illumination



Mural Mixto



Wall surface mounted

LED CE E E E E

IP **30**


CRI **>80** UGR **22**

Expectancy **72000 h.** Efficiency (%) **67**
L70B10

Photobiological safety


RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3 h.




- RAL9016
- RAL7001
- RAL9005

Opal diffuser



Indirect opal diffuser



	W	K	LUMEN	COLOUR	
MM1L3B	1x13,4W	3000	1520 lm	○	1,1
MM1L3G	1x13,4W	3000	1520 lm	●	1,1
MM1L3N	1x13,4W	3000	1520 lm	●	1,1
MM1L4B	1x13,4W	4000	1680 lm	○	1,1
MM1L4G	1x13,4W	4000	1680 lm	●	1,1
MM1L4N	1x13,4W	4000	1680 lm	●	1,1
MM1H3B	1x19W	3000	2320 lm	○	1,1
MM1H3G	1x19W	3000	2320 lm	●	1,1
MM1H3N	1x19W	3000	2320 lm	●	1,1
MM1H4B	1x19W	4000	2580 lm	○	1,1
MM1H4G	1x19W	4000	2580 lm	●	1,1
MM1H4N	1x19W	4000	2580 lm	●	1,1

Direct / Indirect illumination

