



Nora

Nora is the new IP66 projector for outdoors installations. It is available in black and with glass diffuser. Two different powers: 2300 or 5250 lumens.

Nora

Installation	Ceiling surface mounted Wall surface mounted
Diffuser	<input type="radio"/>
Light source	LED
Photobiological safety	0
UGR	22
CRI	>80
MacAdam ellipse	3
Beam angle range	95
Power range (W)	18,2-35,9
Colour temperature (°K)	4000
Light range	2300-5250
Power factor	0,95
Efficiency (%)	86,8
Expectancy	50000 h L70B10
DALI Option	✓
Continuous function 24h	✓
IP	66
Class	I

Opal diffuser



For other CRI values, please contact us.

Nora



Ceiling surface mounted



Wall surface mounted



LED CE ENEC 850°C

IP 66

CRI >80

UGR 22

95°

Expectancy
50000 h.
L70B10

Efficiency (%)
86,8


Photobiological safety

RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk


*Time under 3 h.



Opal diffuser



CO-C180
C90-C270 $\eta=87\%$



● RAL9005

	W	K	LUMEN	Beam spread	COLOUR	Beam spread
NO34ON	1x18,2W	4000	2300 lm	95°	●	1,7
NO54ON	1x35,9W	4000	5250 lm	95°	●	1,7



Compatible with **NormaLINK**

	W	K	LUMEN	Beam spread	COLOUR	Beam spread
NO34DON	1x18,2W	4000	2300 lm	95°	●	1,7
NO54DON	1x35,9W	4000	5250 lm	95°	●	1,7