



# Til

Til is a wall lamp with a minimalist design. One by one or in combination it enables empty spaces to be decorated and flooded with light.

## Til

Installation	Wall surface mounted
Diffuser	
Light source	LED
Photobiological safety	0
UGR	22
CRI	>80
MacAdam ellipse	3
Beam angle range	-
Power range (W)	6
Colour temperature (°K)	3000   4000
Light range	535-615
Power factor	0,5
Efficiency (%)	17,6
Expectancy	36000 h L70B10
DALI Option	-
Continuous function 24h	✓
IP	20
Class	I



For other CRI values, please contact us.



Wall surface mounted  
Direct/Indirect



IP  
**20**

CRI  
**>80**

UGR  
**22**


Expectancy  
**36000 h.**  
L70B10

Efficiency (%)  
**17,6**

Photobiological safety

RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

\*Time under 3 h.



- RAL9016
- RAL7001
- RAL9005

	W	K	LUMEN	COLOUR	⚠
AT3B	1x6W	3000	535 lm	○	0,6
AT3G	1x6W	3000	535 lm	●	0,6
AT3N	1x6W	3000	535 lm	●	0,6
AT4B	1x6W	4000	615 lm	○	0,6
AT4G	1x6W	4000	615 lm	●	0,6
AT4N	1x6W	4000	615 lm	●	0,6

Up to 5 years warranty (prior studying each project)