



Tiny

TINY is a reduced size, high performance swivelling downlight.

Available with white, grey or black ring.



FOR REPLACING LED AND DICHOIC LAMPS
24H UNINTERRUPTED WORKING TIME WITH TOTAL GUARANTEE.

CAN BE MANAGED BY PHASE CUT
(only fittings not dali compatible)

Tiny

Installation	Ceiling recessed mounted
Diffuser	<input type="radio"/>
Light source	LED
Photobiological safety	1
UGR	19
CRI	>80
MacAdam ellipse	3
Beam angle range	66
Power range (W)	5,8
Colour temperature (°K)	3000 4000
Light range	670-700
Power factor	0,94
Efficiency (%)	87,3
Expectancy	60000 h L70B10
DALI Option	✓
Continuous function 24h	✓
IP	20
Class	II
Ideal cut out (mm)	70

Without diffuser



For other CRI values, please contact us.

Tiny



Ceiling recessed mounted



LED CE RoHS 85°C

IP 20

CRI >80

UGR 19

66°


Expectancy
60000 h.
L70B10

Efficiency (%)
87,3

Photobiological safety

RG0	Risk free
RG1*	1 Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3 h.




Minimum ceiling installation height
94

Ideal cut out
Ø70
Circular cut

- RAL9016
- RAL7001
- RAL9005

Without diffuser



WITHOUT PHASE CUT REGULATION

	W	K	LUMEN	COLOUR	⚡	PACKAGING
TI03SB	1x5,8W	3000	670 lm	○	0,1	10
TI03SG	1x5,8W	3000	670 lm	●	0,1	10
TI03SN	1x5,8W	3000	670 lm	●	0,1	10
TI04SB	1x5,8W	4000	700 lm	○	0,1	10
TI04SG	1x5,8W	4000	700 lm	●	0,1	10
TI04SN	1x5,8W	4000	700 lm	●	0,1	10

REGULATION BY PHASE CUT

	W	K	LUMEN	COLOUR	⚡	PACKAGING
TI03B	1x5,8W	3000	670 lm	○	0,1	10
TI03G	1x5,8W	3000	670 lm	●	0,1	10
TI03N	1x5,8W	3000	670 lm	●	0,1	10
TI04B	1x5,8W	4000	700 lm	○	0,1	10
TI04G	1x5,8W	4000	700 lm	●	0,1	10
TI04N	1x5,8W	4000	700 lm	●	0,1	10



Compatible with **NormaLINK**

	W	K	LUMEN	COLOUR	⚡	PACKAGING
TI03DB	1x5,8W	3000	670 lm	○	0,1	10
TI03DG	1x5,8W	3000	670 lm	●	0,1	10
TI03DN	1x5,8W	3000	670 lm	●	0,1	10
TI04DB	1x5,8W	4000	700 lm	○	0,1	10
TI04DG	1x5,8W	4000	700 lm	●	0,1	10
TI04DN	1x5,8W	4000	700 lm	●	0,1	10