



Uro



Uro

Installation	Ceiling/wall surface mounted
Diffuser	Opal
Light source	LED
Photobiological safety	0
UGR	22
CRI	>80
MacAdam ellipse	3
Beam angle range	112
Power range (W)	12,6
Colour temperature (°K)	3000 4000
Light range	1620-1770
Power factor	0,9
Efficiency (%)	76,5
Expectancy	50000 h L70B10
DALI Option	✓
Continuous function 24h	✓
IP	65
IK	10
Class	II



IP	IK
65	10

CRI	UGR
>80	22


Photobiological safety	
RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3h.

Expectancy	Efficiency (%)
50000 h. L70B10	76,5

- RAL9016
- RAL7001
- RAL9005

Opal diffuser




ACCESSORY

AUKM

Semi recessed URO installation kit

X2



Compatible with **NormaLINK**

	W	K	LUMEN	COLOUR	⚠
AU23DB	1x12,6W	3000	1620 lm	○	1,4
AU23DG	1x12,6W	3000	1620 lm	●	1,4
AU23DN	1x12,6W	3000	1620 lm	●	1,4
AU24DB	1x12,6W	4000	1770 lm	○	1,4
AU24DG	1x12,6W	4000	1770 lm	●	1,7
AU24DN	1x12,6W	4000	1770 lm	●	1,4

	W	K	LUMEN	COLOUR	⚠
AU23B	1x12,6W	3000	1620 lm	○	1,4
AU23G	1x12,6W	3000	1620 lm	●	1,4
AU23N	1x12,6W	3000	1620 lm	●	1,4
AU24B	1x12,6W	4000	1770 lm	○	1,4
AU24G	1x12,6W	4000	1770 lm	●	1,4
AU24N	1x12,6W	4000	1770 lm	●	1,4