



Zafiro

ZAFIRO is a small-sized spatial system. Specially designed for LED light sources, made of aluminium profile.

Zafiro


Installation	Ceiling surface mounted Ceiling suspended mounted
Diffuser	○
Light source	LED
Photobiological safety	0
UGR	22
CRI	>80
MacAdam ellipse	3
Beam angle range	100
Power range (W)	26,8-57
Colour temperature (°K)	3000 4000
Light range	3040-7740
Power factor	0,95
Efficiency (%)	54,2
Expectancy	72000 h L70B10
DALI Option	✓
Continuous function 24h	✓
IP	30
Class	I

○ Opal diffuser



For other CRI values, please contact us.

Zafiro



IP 30

CRI >80

UGR 22

100°


Expectancy
72000 h.
L70B10

Efficiency (%)
54,2

Photobiological safety


RG0	0 Risk free
RG1*	Low risk
RG2	Moderate risk
RG3	High risk

*Time under 3 h.



- RAL9016
- RAL7001

Opal diffuser



DALI REGULATION AVAILABLE

	W	K	LUMEN	COLOUR	L(mm)	IP
Z4L30B	1x26,8W	3000	3040 lm	○	1180	2,0
Z4L30G	1x26,8W	3000	3040 lm	●	1180	2,0
Z4L40B	1x26,8W	4000	3360 lm	○	1180	2,0
Z4L40G	1x26,8W	4000	3360 lm	●	1180	2,0
Z4H30B	1x38W	3000	4640 lm	○	1180	2,0
Z4H30G	1x38W	3000	4640 lm	●	1180	2,0
Z4H40B	1x38W	4000	5160 lm	○	1180	2,0
Z4H40G	1x38W	4000	5160 lm	●	1180	2,0
Z6L30B	1x40,2W	3000	4560 lm	○	1740	2,9
Z6L30G	1x40,2W	3000	4560 lm	●	1740	2,9
Z6L40B	1x40,2W	4000	5040 lm	○	1740	2,9
Z6L40G	1x40,2W	4000	5040 lm	●	1740	2,9
Z6H30B	1x57W	3000	6960 lm	○	1740	2,9
Z6H30G	1x57W	3000	6960 lm	●	1740	2,9
Z6H40B	1x57W	4000	7740 lm	○	1740	2,9
Z6H40G	1x57W	4000	7740 lm	●	1740	2,9

ACCESSORIES

Suspension accessory

	L (m)	COLOUR
1029L2	2	●
1029L4	4	●

